



REV.	DATE	DESCRIPTION OF CHANGE	BY	APP'D
A	5-20-94	ADD PERFORM. TABLE CHANGE FLUOT.	RCS	KCM 6-8-95
B	5-22-97	REVISED FOR NEW MODEL. MOUNTING PORTS CHANGED TO 1/2" OR 5/8" VANES. REVISED FOR NEW STYLE HOUSING.	KCM	RCS 6-8-97 WV 2-19-04
C	1-15-04	REVISED FOR NEW MODEL. MOUNTING PORTS CHANGED TO 1/2" OR 5/8" VANES. REVISED FOR NEW STYLE HOUSING.	MEA	2-19-04

ALL DIMENSIONS ARE IN MILLIMETERS

PUMP CAPACITY @ 1450 RPM	
FLOW RATE	PRESSURE RANGE
48 AND 80 LPH	0 TO 1380 KPa
111 TO 445 LPH	0 TO 1720 KPa

NOTES:
 ⚠️ SHAFT SIZE IS 11.07/11.05 ϕ .
 ⚠️ FOR REVERSE ROTATION PUMP, THE RELIEF VALVE WOULD BE LOCATED ON THE OPPOSITE SIDE AND THE INLET PORT, OUTLET PORT, FLOW DIRECTION ARROWS, AND NAMEPLATE ARROW WOULD BE REVERSED.

MATERIAL		THIRD ANGLE PROJECTION	
UNLESS OTHERWISE SPECIFIED: REMOVE BURRS AND SHARP EDGES. MACHINED SURFACE ROUGHNESS 3.2 MICROMETERS Ra.			
DIMENSIONS ARE REFERENCE		Procon Products A Division of Foshin Industries 11000 Highway 5725 Waukegan, Illinois 60087	
THE DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE EXCLUSIVE PROPERTY OF PROCON. IT IS TO BE USED ONLY FOR THE PURPOSES AUTHORITY OF PROCON.		TITLE: OUTLINE, PUMP-SERIES "3" MOUNTING "A" SCALE: FULL DRAWN: KGM DATE: 10-1-90 CHECKED: RCS DATE: 10-22-90 DO NOT SCALE DRAWING	
		SHEET 1 OF 1	