



REV.	DATE	DESCRIPTION OF CHANGE	BY	APP'D
A	5-25-94	ADD PERF. TABLE CHANGE TO 250 PSI CHANGE FLUT AND SHAFT BLDT	RCS	KGM
B	5-21-97	REVISED FOR NEW MODEL #10,400 RPM	RCS	KGM
C	12-9-03	REVISED FOR NEW MODEL #10,400 RPM AND SINGLE RING INSE	MEA	12-10-03

ALL DIMENSIONS ARE IN MILLIMETERS

(A)B	PUMP CAPACITY @ 1450 RPM
	FLOW RATE
	PRESSURE RANGE
	48 AND 80 LPH
	0 TO 1380 KPa
	111 TO 445 LPH
	0 TO 1720 KPa

NOTES:  
 1 CLEARANCE REQUIRED FOR STRAINER REMOVAL.  
 2 DIMENSION IS WIDTH OF SLOT IN PUMP SHAFT.

MATERIAL		THIRD ANGLE PROJECTION	
UNLESS OTHERWISE SPECIFIED: REMOVE BURRS AND SHARP EDGES. MACHINED SURFACE ROUGHNESS 3.2 MICROMETERS Ra. TOLERANCES: DIMENSIONS ARE REFERENCE			
THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE EXCLUSIVE PROPERTY OF PROCON PRODUCTS. IT IS TO BE KEPT IN CONFIDENTIAL FORM, WITHOUT THE EXPRESS WRITTEN AUTHORITY OF PROCON.		<b>Procon Products</b> A Division of Procon Industries 1143 Procon Blvd. Murfreesboro, TN 37132	
TITLE	SCALE	DATE	DATE
OUTLINE, PUMP-SERIES "A" MOUNTING "B"	FULL	10-17-90	10-22-90
		2072	
DO NOT SCALE DRAWING			