



PUMP CAPACITY @ 1450 RPM	
FLOW RATE	PRESSURE RANGE
48 AND 80 LPH	0 TO 1380 KPa
111 TO 445 LPH	0 TO 1720 KPa

NOTES:
 ▲ DIMENSION IS WIDTH OF SLOT IN PUMP SHAFT.
 ▲ FOR REVERSE ROTATION PUMP, THE RELIEF VALVE WOULD BE LOCATED ON THE OPPOSITE SIDE AND THE INLET PORT, OUTLET PORT, FLOW DIRECTION ARROWS, AND NAMEPLATE ARROW WOULD BE REVERSED.

MATERIAL		UNLESS OTHERWISE SPECIFIED: REMOVE BURRS AND SHARP EDGES. MACHINED SURFACE ROUGHNESS 3.2 MICROMETERS Ra. TOLERANCES: DIMENSIONS ARE REFERENCE	
THIRD ANGLE PROJECTION		THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE EXCLUSIVE PROPERTY OF PROCON PRODUCTS. IT IS TO BE USED ONLY FOR THE PURPOSES SPECIFIED OR REPRODUCED IN ANY FORM, WITHOUT THE EXPRESS WRITTEN AUTHORITY OF PROCON.	
Procon Products A Division of Procon Industries 11400 Highway 212 Murfreesboro, Tennessee 37132		TITLE: OUTLINE, PUMP--SERIES 3" MOUNTING "B" SCALE: 1/2" OR 5/8" VANE PUMP DRAWN: KGM CHECKED: RCS DATE: 10-17-90 DATE: 10-22-90 DRAWING NO.: 2073 SHEET: 1 OF 1	

REV.	DATE	DESCRIPTION OF CHANGE	BY	APP'D
A	1-6-94	CHANGED SLOT DIA., CHANGED SLOT TOL. AND PERFORMANCE TABLE	RCS	KGM 6-8-95
B	5-22-97	REVISED FOR NEW MODEL. NEW MODEL PERFORMANCE TABLE TO LEFT @ 1450 RPM	RCS	RCS 6-11-97
C	2-20-04	REVISED PERFORM. TABLE TO LEFT @ 1450 RPM. NEW MODEL PERFORMANCE TABLE TO RIGHT	MEA	2-23-04

ALL DIMENSIONS ARE IN MILLIMETERS