



REV.	DATE	DESCRIPTION OF CHANGE	BY	APP'D
A	1-6-94	CHANGED SLOT DIA., CHANGED SLOT TOL.	RCS	KGM
B	5-22-97	ADDED PERFORMANCE TABLE	RCS	KGM
C	2-20-04	REVISED FOR NEW MODEL NUMBER	ME A	2-23-04

PUMP CAPACITY @ 1725 RPM	
FLOW RATE	PRESSURE RANGE
15 AND 25 GPH	0 TO 200 PSI
35 TO 140 GPH	0 TO 250 PSI

NOTES:
 ▲ DIMENSION IS WIDTH OF SLOT IN PUMP SHAFT.
 ▲ FOR REVERSE ROTATION PUMP, THE RELIEF VALVE WOULD BE LOCATED ON THE OPPOSITE SIDE AND THE INLET PORT, OUTLET PORT, FLOW DIRECTION ARROWS, AND NAMEPLATE ARROW WOULD BE REVERSED.

MATERIAL		THIRD ANGLE PROJECTION	
UNLESS OTHERWISE SPECIFIED: REMOVE BURRS AND SHARP EDGES. MACHINED SURFACE ROUGHNESS 125 MICROINCHES Ra. TOLERANCES: DIMENSIONS ARE REFERENCE			
THE DRAWING CONTAINS CONFIDENTIAL INFORMATION AND IS THE EXCLUSIVE PROPERTY OF PROCON PRODUCTS. IT IS TO BE KEPT IN CONFIDENTIAL FORM, WITHOUT THE EXPRESS WRITTEN AUTHORITY OF PROCON.		Procon Products A Division of Procon Industries 125 W. WILSON ST. MEMPHIS, TENNESSEE 38122	
TITLE: OUTLINE, PUMP-SERIES 3" MOUNTING "B" 1/2" OR 5/8" VANE PUMP		SCALE: FULL	DATE: 10-17-90
DRAWN: KGM		CHECKED: RCS	DATE: 10-22-90
DO NOT SCALE DRAWING		SHEET: 1	OF: 1